

Product Specifications Swing Gate Barrier (Model SG-MAN-1200) Stops 15,000 lbs. at 50 mph Impact

1. Certified with ASTM F2656-07 M50 rating (K12), stops 15,000 lb. vehicle impact at 50 mph.
2. Department of Defense (DoD) approved and listed on the Anti-Ram Vehicle Barrier List.
3. One (1) person manually opens & closes light-weight gate.
4. Custom gate heights from 8 feet to 24 feet.
5. Gate lathing and locking mechanism.
6. Quick installation in about 1-1/2 days. Only 3 modular prefabricated system components.
7. Connect any adjacent perimeter security barriers. This includes fences, concrete blocks, jersey barriers, cable barriers, or other perimeter security systems.
8. Robust gate is a free-standing barrier, and independent of adjacent attachments.
9. Gate can swing open up to 160 degrees. Drop down pin to secure gate in opened position.
10. End supports are reusable after massive impacts. A replacement gate is easily rehung on Gorilla bearing hinges.
11. All weather uses.
12. Minimal maintenance and simple to use.
13. Optional electric model with custom controls and alarms. Power requirement is one 220/220/230volt, 20amp single phase.
14. Optional custom colors, placards, signs, markings, and hot dipped galvanized finish.