## SET & POUR BOLLARD MODEL SPB-1200



Prefabricated Single Bollard Unit

ASTM M50 (K12) CERTIFIED

NO REBAR IN FOUNDATION

- ♦ Department of Defense (DoD) approved and listed on Anti-Ram Vehicle Barrier List.
- ♦ One single standalone bollard stops 15,000 lb. vehicle at 50 mph with 1.2 meters penetration.
- ♦ 2+ bollard array is ASTM M50 P1 (K12) certified. Vehicle penetration less than 1 meter.
- Unrestricted bollard spacing (any distance), while maintaining ASTM M50 P1 certification. (fewer bollards results in less costs)
- ♦ Simply set single prefabricated bollard in excavation and pour concrete (no rebar in foundation).
- No tying, bolting, welding, assembly, or specialty subgrade required.
- Excavation 48" wide by 36" deep with 4000 psi concrete.
- Easy to install with turns and across grade elevation changes using standard bollard.
- ♦ Allows for field adjustment.
- ♦ Reduce installation time and cost by about 50%.
- ♦ Bi-directional stopping capability.
- Removeable bollard configuration is available.
- Variety of bollard covers are available including stainless steel, plastic, decorative shapes, concrete, lighted covers, and others
- Drawings, submittals, engineering support, and installation instructions with photos are included.













**www.barrier1.us** (336) 617-8478 phone (336) 617-8471 fax